Author Index

Alcock, R. J.	Artificial intelligence based techniques for processing segmented images of wood boards	119–129
Al-Hassani, S. T. S.	Investigation into the effect of circumferential through-wall slits on a cantilevered pipe subjected to a transverse end load	163–170
Allsopp, K.	Reliability prediction procedures for mechanical components at the design stage	213–224
Amini, A.	A study of hydraulic impacts caused by condensate in steam distribution systems	1–6
Błachut, J.	Analysis and collapse of thick composite torispheres	103–117
Bradley, M. S. A.	Design of small-rate feeders for non-free-flowing materials: a case study	81–87
Chan, G. C. M.	An experimental study of the collapse of horizontal saddle-supported storage vessels	183–195
Dawson, M. J.	Design of small-rate feeders for non-free-flowing materials: a case study	81–87
Dietz, P.	Vibrational power flow in beam-plate structures with isolation components	89–101
Dong, L.	Analysis and collapse of thick composite torispheres	103–117
Fessler, H.	Effect of changes in the taper-hub shape on the strength of high-pressure flanges	151–162
Galletly, G. D.	Elastic buckling of imperfect circular toroidal shells under external pressure	197–209
Geominne, J.	A method of plant design evaluation featuring maintainability and reliability	71–80
Grosvenor, R. I.	Process plant condition monitoring and fault diagnosis	13–30
Gummer, J. H.	Venturi investigations into cavitation in ethylene glycol/water mixtures	235–250
Hagemeijer, P. M.	A methodology for risk-based inspection of pressurized systems	37–47
Hagemeijer, P. M.	Application of risk-based inspection for pressurized HC production systems in a Brunei petroleum company	49–54
Hanks, B. J.	An appreciation of common cause failures in reliability	31–35
Hu, X.	Vibrational power flow in beam-plate structures with isolation components	89–101
Hyde, T. H.	Creep of welded pipes	171–182
Kerveld, G.	A methodology for risk-based inspection of pressurized systems	37–47
Kerveld, G.	Application of risk-based inspection for pressurized HC production systems in a Brunei petroleum company	49–54
Klausner, J. F.	Two-phase jet impingement for non-volatile residue removal	271–279
Lochegnies, D.	An inverse method for prediction of the required temperature distribution in the creep forming process	7–11
Macfarlane, D. M.	Metal-to-metal full face taper-hub flanges: finite element model evaluation and preliminary plastic analysis results	57–69
Martin, P.	A review of mechanical reliability	281–287
Mei, R.	Two-phase jet impingement for non-volatile residue removal	271–279
Moreau, P.	An inverse method for prediction of the required temperature distribution in the creep forming process	7–11
Near, S.	Two-phase jet impingement for non-volatile residue removal	271–279
Neilson, R. D.	Load cell for dynamic measurement of cutting forces generated during ultrasonic drilling and milling of hard materials	263–270
Oudin, J.	An inverse method for prediction of the required temperature distribution in the creep forming process	7–11
Owen, I.	A study of hydraulic impacts caused by condensate in steam distribution systems	1–6
Perry, D. A.	Effect of changes in the taper-hub shape on the strength of high-pressure flanges	151–162
Pham, D. T.	Artificial intelligence based techniques for processing segmented images of wood boards	119–129
Pittman, A. N.	Design of small-rate feeders for non-free-flowing materials: a case study	81–87
Player, M. A.	Load cell for dynamic measurement of cutting forces generated during ultrasonic drilling and milling of hard materials	263–270
Reid, S. R.	Non-linear dynamic analysis of cantilever whipping pipes	133–149
Sharif, M. A.	Process plant condition monitoring and fault diagnosis	13–30
Spence, J.	Metal-to-metal full face taper-hub flanges: finite element model evaluation and preliminary plastic analysis results	57–69
Spence, J.	An experimental study of the collapse of horizontal saddle-supported storage vessels	183–195
Stephens, D. J.	A study of hydraulic impacts caused by condensate in steam distribution systems	1–6
Stith, R.	Two-phase jet impingement for non-volatile residue removal	271–279
Strutt, J. E.	Reliability prediction procedures for mechanical components at the design stage	213–224
Sun, W.	Creep of welded pipes	171–182

© IMechE 1998

Thew, M. T.	Venturi investigations into cavitation in ethylene glycol/water mixtures	235–250
Thompson, G.	A method of plant design evaluation featuring maintainability and reliability	71–80
Tooth, A. S.	Metal-to-metal full face taper-hub flanges: finite element model evaluation and preliminary plastic analysis results	57–69
Tooth, A. S.	An experimental study of the collapse of horizontal saddle-supported storage vessels	183–195
Vartdal, B.	Investigation into the effect of circumferential through-wall slits on a cantilevered pipe subjected to a transverse end load	163–170
Wang, J.	A review of design for safety methodology for large marine and offshore engineering systems	251–261
Warburton, D.	Reliability prediction procedures for mechanical components at the design stage	213–224
Wiercigroch, M.	Load cell for dynamic measurement of cutting forces generated during ultrasonic drilling and milling of hard materials	263–270
Wilkinson, D.	The hot plate impactor: a novel instrument for continuous characterization of liquid sprays	225–233
Williams, J. R. R.	A method of plant design evaluation featuring maintainability and reliability	71–80
Yang, J. L.	Non-linear dynamic analysis of cantilever whipping pipes	133–149
Yi, C.	Vibrational power flow in beam-plate structures with isolation components	89–101

© IMechE 1998